
# DEFINITIVE SUBDIVISION PLAN BOUTILIER ROAD IN LEICESTER, MASSACHUSETTS MARCH 20, 2019



# APPLICANT:

ZPT ENERGY SOLUTIONS II, LLC BRENDON GOVE 6 PARK AVENUE WORCESTER, MASSACHUSETTS 01605 TEL: (774) 314-2549

## **OWNER**


NICHOLAS A. CASELLO 21 BOUTILIER ROAD LEICESTER, MASSACHUSETTS 01524


# CIVIL ENGINEER & LAND SURVEYOR:


HANNIGAN ENGINEERING, INC. 8 MONUMENT SQUARE LEOMINSTER, MASSACHUSETTS 01453 TEL: (978) 534-1234


### PLAN INDEX


SHEET	1	INDEX PLAN
SHEET	2-5	PLAN OF LAND
SHEET	6-8	DEFINITIVE SUBDIVISION PLAN
SHEET	9	ROADWAY PROFILE
SHEET	10-11	CONSTRUCTION DETAILS























APPLICANT:

ZPT ENERGY SOLUTIONS II, LLC
BRENDON GOVE, MANAGER
6 PARK AVENUE
WORCESTER, MASSACHUSETTS 01605

OWNER:

NICHOLAS A. CASELLO
21 BOUTILIER ROAD
LEICESTER, MASSACHUSETTS 01524

REFERENCES:
ASSESSORS INFORMATION:
MAP 35, PARCELS B3

MPA35 PARCEL B/2 DEED: BOOK 39509, PAGE 087

DEED: BOOK 42787, PAGE 182

### PROJECT INFORMATION

LAND INFORMA
MAP/PARCEL:
DEED BOOK/PAGE:

35/B/3; 35/B/2 42787/182; 39509/087

ZONING INFORMATION SUBURBAN BUSINESS ZONING DISTRICT: RESIDENTIAL-1 (BR-1) AGRICULTURAL (SA) DIMENSIONAL REQUIREMENTS: MINIMUM AREA: 80,000 SF 200 FEET MINIMUM FRONTAGE: 150 FEET MAXIMUM HEIGHT: 55 FEET 35 FEET MINIMUM SETBACKS: FRONT YARD:

40 FT

40 FT

40 FT

40 FT

GENERAL NOTES:

SIDE YARD:

REAR YARD:

1. PROPERTY LINE INFORMATION BASED DEEDS AND PLANS OF RECORD.
NO CERTIFICATION OF PROPERTY LINES SHOWN ON THIS PLAN IS INTENDED
OR IMPLIED BY HANNIGAN ENGINEERING, INC. PROPERTY LINE
DETERMINATIONS MADE BY A ON—THE—GROUND PROPERTY LINE SURVEY IN
JULY OF 2018.

2. TOPOGRPHIC SURVEY INFORMATION AS DEPICTED HERON IS BASED ON LIDAR (LIGHT DETECTION AND RANGING) OBSERVATION MADE AND PROCESS BY WOLPERT, INC. IN 2014 AND PROVIDED BY THE US GEOLOGICAL SURVEY. POST—PROCESSING BY OTHERS AND PROVIDED TO THIS OFFICE. DATUM IS BASED ON NAVD88.

3. AREAS SUBJECT TO PROTECTION UNDER THE WETLANDS PROTECTION ACT HAVE BEEN DELINEATED BY CARON ENVIRONMENTAL IN JULY OF 2018. THESE AREAS ARE DEPICTED ON THE PLANS BASED ON FIELD SURVEY LOCATION DURING THE TOPOGRAPHIC SURVEY.

4. LOCATION OF ALL UTILITIES ARE APPROXIMATE AS SHOWN AND BASED UPON VISIBLE STRUCTURES AT THE TIME OF THE FIELD SURVEY. LOCATION OF EXISTING UTILITIES AND SUBSURFACE STRUCTURES, WHETHER OR NOT SHOWN ON THESE PLANS, SHALL BE DETERMINED BY THE CONTRACTOR, MARKED IN THE FIELD, AND REVIEWED BY THE ENGINEER PRIOR TO THE COMMENCEMENT OF CONSTRUCTION. THE CONTRACTOR SHALL BE AWARE OF THE OBLIGATION TO ALL UTILITY COMPANIES AND AGENCY AS WELL AS DIG—SAFE PRIOR TO EXCAVATION. (SEE NOTE)

5. NOTIFICATION REQUIREMENTS SHOWN ON THIS PLAN SHALL NOT RELIEVE THE CONTRACTOR OF ANY OTHER REQUIREMENTS WHICH MAY EXIST UNDER LOCAL, STATE, OR FEDERAL JURISDICTION TO WHICH THE CONTRACTOR IS ORUGATED.

6. RELOCATION OF AND/OR CONNECTION TO EXISTING UTILITIES SHALL BE PERFORMED IN ACCORDANCE WITH PROVISIONS OF THE APPROPRIATE UTILITY COMPANY AND/OR REGULATORY AGENCY.
7. UNLESS OTHERWISE SPECIFIED, ALL MATERIALS AND WORKMANSHIP SHALL

CONFORM WITH THE REQUIREMENTS OF THE CITY OF LEICESTER AND THE MASS DOT SPECIFICATIONS OF HIGHWAYS AND BRIDGES.

8. ALL SLOPES UNLESS OTHERWISE SPECIFIED, SHALL BE LOAMED AND SEEDED FOR STABILIZATION.

9. ANY DEVIATIONS IN DESIGN AS SHOWN SHALL REQUIRE A REVIEW AND APPROVAL OF THE DESIGN ENGINEER OR FIRM. CHANGES MADE IN THE FIELD MADE WITHOUT AUTHORIZATION SHALL BE SUBJECT TO REVIEW BY THE ENGINEER AND APPROPRIATE APPROVING AUTHORITY. EXPENSES INCURRED TO BRING THE UNAUTHORIZED CHANGES TO ACCEPTABLE CONFORMANCE SHALL BE BORNE BY THE COMPANY OR CONTRACTOR MAKING THE UNAUTHORIZED CHANGE.

10. ANY MATERIALS DISCOVERED ON-SITE WHICH ARE NOT SUITABLE FOR USE IN THE PROJECT AS SHOWN ON THIS PLAN SHALL BE REMOVED AND HAULED OFF-SITE TO AN APPROPRIATELY LICENSED FACILITY.

11. PLANS TO BE REVIEWED BY APPLICABLE UTILITY AGENCIES FOR COMPLIANCE WITH REGULATIONS. FINAL LOCATION IS SUBJECT TO CHANGE.

12. APPLICANT SHOULD BE AWARE OF OBLIGATIONS TO COMPLY WITH CHAPTER 131. SECTION 40 OF THE MASSACHUSETTS GENERAL LAWS,

OTHERWISE KNOWN AS THE WETLANDS PROTECTION ACT, AND THE ASSOCIATED REGULATIONS (310 CMR 10.00)

13. STOCKPILING OF MATERIAL SHALL NOT BE PERMITTED WITHIN ANY AREAS SUBJECT TO PROTECTION UNDER THE WETLANDS PROTECTION ACT WITHOUT PRIOR APPROVAL BY THE LOCAL CONSERVATION COMMISSION. STOCKPILES SHALL BE PLACED IN A SUITABLE LOCATION AND SURROUNDED BY A ROW

OF STAKED HAY BALES FOR EROSION CONTROL.

14. AREAS OF FILL TO BE COMPACTED TO A MINIMUM 95% DRY DENSITY IN AREAS WITHIN ROADWAYS AND UTILITY EASEMENTS. OTHER AREAS OF FILL TO BE COMPACTED TO A MINIMUM 90% DRY DENSITY. ALL FILL MATERIALS ARE TO BE CLEAN FILL, FREE OF DELETERIOUS MATERIALS AND DEBRIS.


15. THE AREA PROPOSED FOR DEVELOPMENT IS NOT WITHIN A 100 YEAR FLOOD PLAIN PER F.E.M.A. FIRM PANEL #25027C-0784E, DATED: JULY 04, 2011. COMPLIANCE WITH APPLICABLE REGULATIONS IS REQUIRED.

16. PRE-CONSTRUCTION CONFERENCE SHALL BE HELD PRIOR TO THE

COMMENCEMENT OF CONSTRUCTION.

17. ALL UTILITIES ARE TO BE INSTALLED BY A LICENSED UTILITY CONTRACTOR LICENSED BY THE CITY OF LEICESTER.

# DEFINITIVE PLAN



#### HANNIGAN ENGINEERING, INC.

CIVIL ENGINEERS & LAND SURVEYORS

8 MONUMENT SQUARE LEOMINSTER, MASSACHUSETTS 01453 (978) 534-1234 (T) (978) 534-6060 (F)


# ROADWAY PROFILE

LEICESTER, MASSACHUSETTS

PREPARED FOR:
ZPT ENERGY SOLUTIONS II, LLC
BRENDON GOVE
6 PARK AVENUE

WORCESTER, MASSACHUSETTS, 01605 TEL: (774) 314-2549

GRAPHIC SCALE: 1"=40'



#### EXISTING RIGHT OFFSET -EXISTING CENTERLINE -EXISTING LEFT OFFSET 920 DCB#1 \_\_\_\_\_ 0+25 19.75L 0+45 5.82R RIM=899.7± INV=896.6± RIM=900.7± ArrGRADE BREAK STA = 1+76.88 INV=895.4±(IN) INV=895.25±(OUT) SUMP=892.6± ELEV = 905.73DCB#2 0+25 19.75R HG4 HYDROWORK UNIT RIM=899.7± GRADE BREAK STA = -0+05.00ELEV = 898.91 SUMP=892.6± 15" HDPE L=215FT S=0.005F/F 12" HDPE— L=28FT S=0.007 F/F 12" HDPE L=21 FT (LOCATED OUTSIDE ROW) INV=895.2±(IN) INV=895.1±(OUT) DISCHARGE PIPE TO ---S=0.010 F/F DETENTION BASIN -0+21 0+00 1+00 1+77 **ROADWAY PROFILE** HORIZONTAL SCALE = 1:40

**VERTICAL SCALE = 1:8** 

#### EROSION & SEDIMENTATION CONTROL PLAN

GENERAL:

. THE PURPOSE OF THIS PLAN IS TO PRESENT A PREVENTIVE METHOD OF CONSTRUCTION TO MINIMIZE THE IMPACT OF THE CONSTRUCTION ACTIVITIES UPON WETLAND AND OTHER SENSITIVE AREAS. THE DATA CONTAINED ON THIS PLAN IS INTENDED TO SUPPLEMENT THE DEVELOPER OR CONTRACTORS' EXPERTISE AND IS NOT MEANT TO CIRCUMVENT LOGICAL DECISIONS REQUIRED BY A VARIETY OF FIELD CONDITIONS INCLUDING WEATHER AND THE TYPE OF EQUIPMENT AVAILABLE TO THE

THE CONTRACTOR IS TO BE AWARE OF THE REQUIREMENTS AND OBLIGATIONS TO COMPLY WITH CHAPTER 131, SECTION 40 OF THE MASSACHUSETTS GENERAL LAWS, OTHERWISE KNOWN AS THE WETLANDS PROTECTION ACT, AND ITS ASSOCIATED REGULATIONS (310 CMR 10.00). CERTAIN PERMITS IN THE FORM OF AN ORDER OF CONDITIONS, OR OTHER FORMAT, MAY BE REQUIRED FOR THE CONSTRUCTION AS DEPICTED ON THIS PLAN. THESE PERMITS SHALL BE REVIEWED AND ADHERED TO BY THE CONTRACTOR THROUGHOUT THE CONSTRUCTION PROCESS. THE CONTRACTOR SHALL ALSO MAINTAIN COPIES OF ALL PERMITS ON SITE

3. IF CHANGES IN THE PROJECT ARE REQUIRED DUE TO FIELD CONDITIONS THE DEVELOPER/CONTRACTOR SHALL PROMPTLY NOTIFY THE ENGINEER FOR REVIEW OF THESE CONDITIONS. UPON REVIEW, AND PRIOR TO THE IMPLEMENTATION OF ANY CHANGE, THE CONTRACTOR AND THE ENGINEER SHALL MEET WITH THE APPROPRIATE LOCAL AND OR STATE OFFICIAL, OR ITS AGENT, TO DETERMINE IF THE CHANGE REQUIRES MODIFICATION TO EXISTING APPROVED PERMITS.

A. ALTERATION AND/OR DESTRUCTION OF WETLAND AREAS WITHOUT PRIOR CONSENT OF THE CONSERVATION COMMISSION IS PROHIBITED. SILTATION PLUMES. ILLICIT DISCHARGES. OR INADVERTANT ALTERATION SHALL BE CONSIDERED AS ACTIVITIES NOT PERMITTED BY THE ORDER AND SHALL BE REPORTED TO THE CONSERVATION COMMISSION ALONG WITH THE PROPOSED MITIGATIVE MEASURES.

PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, THE EROSION AND SEDIMENT CONTROL BARRIER SHALL BE INSTALLED AS SHOWN ON THE PLANS. THE CONTRACTOR SHALL MAINTAIN THE EROSION CONTROL BARRIER UNTIL ALL WORK IS COMPLETE AND ALL AREAS HAVE BEEN STABILIZED. THE REMOVAL OF SEDIMENT CONTROL DEVICES SHALL BE ONLY UPON THE APPROVAL OF THE CONSERVATION COMMISSION.

EROSION AND SEDIMENTATION CONTROL DEVICES, SUCH AS CHECK DAMS, SEDIMENT BASINS, ETC. ARE TO BE INSTALLED AS SHOWN ON THE SITE DEVELOPMENT PLANS WITH ASSOCIATED DETAILS, AS APPROPRIATE.

CONSTRUCTION OPERATIONS SHALL NOT CAUSE NOTICEABLE SEDIMENTATION PLUMES TO OCCUR ON OR SURROUNDING THE PROJECT. SHOULD SEDIMENT EXTEND BEYOND THE EROSION CONTROL BARRIERS, THE CONTRACTOR SHALL STOP WORK AND INSTALL ADDITIONAL MITIGATION MEASURES TO PREVENT FURTHER SEDIMENTATION.

R. NO MATERIAL SUBJECT TO EROSION SHALL BE STOCKPILED OVERNIGHT WITHIN 100 FEET OF ANY WETLAND AREAS WITHOUT PROPER EROSION AND SEDIMENTATION DEVICES IN PLACE.

9. EQUIPMENT SHALL NOT BE PARKED WITHIN WETLAND OR BUFFER AREAS EXCEPT DURING ACTUAL OPERATIONS REQUIRING SAID EQUIPMENT

O. ACCUMULATED SEDIMENT ALONG EROSION CONTROL BARRIERS SHALL BE PERIODICALLY REMOVED AND DISPOSED OF BY THE CONTRACTOR AS REQUIRED BY THE CONSERVATION COMMISSION OR AS DIRECTED BY THE

#### EROSION CONTROL METHODS:

. IT IS OF GREAT IMPORTANCE THAT CONCENTRATION OF RUNOFF BE AVOIDED IN ORDER TO PREVENT THE TRANSPORT OF SEDIMENT.

THE PRIMARY EROSION CONTROL METHOD TO BE UTILIZED IS TO LIMIT THE AREA OF DISTURBANCE DURING CONSTRUCTION ACTIVITIES. THIS IS ACCOMPLISHED BY PROMPT STABILIZATION OF DISTURBED AREAS UPON COMPLETION OF SEQUENCES OF CONSTRUCTION.

EROSION AND SEDIMENT CONTROL DEVICES SUCH AS HAY BALES, SIL FENCES, DIVERSION BERMS, ETC. SHALL BE UTILIZED FOR THE PROTECTION OF THE AREAS BEYOND THE LIMIT OF CONSTRUCTION.

#### DEMARCATION OF SENSITIVE AREAS:

. IT IS RECOMMEND THAT BARRIERS BE PLACED ON THE SITE TO CONTROL THE LIMITS OF THE DISTURBANCE. AS AN EXAMPLE, HAY BALE BARRIERS PROVIDE SUCH DEMARCATION AND OTHER METHODS SUCH AS LOG BARRIERS, ROPE WITH FLAGGING, ETC. MAY BE UTILIZED. CARE SHOULD BE TAKEN IN THE OPERATION OF EQUIPMENT, SUCH

. ACCESS TO THE SITE SHALL BE MADE IN THE AREA OF A PERMANENT DRIVEWAY OR ROADWAY UNLESS DOING SO WOULD RESULT IN A TRAFFIC

THAT ONLY THE MINIMUM AREA NEEDED TO BE ALTERED IS DISTURBED.

P. AN AREA OF CRUSHED STONE SHALL BE PLACED AT THE DRIVEWAY ENTRANCE TO INSURE THAT MUD IS NOT TRACKED ONTO THE EXISTING ROAD (SEE CONSTRUCTION ENTRANCE DETAIL). IF MUD IS INADVERTENTLY TRACKED ONTO THE ROAD, IT SHOULD BE PROMPTLY REMOVED.

LABORERS VEHICLES SHALL BE PARKED IN A DESIGNATED AREA AS O MINIMIZE DISTURBED SURFACES AND TO INSURE THAT RUTS ARE NOT CREATED AND WHICH COULD CARRY WATER TO A WETLAND OR OTHER

. SUITABLE MEASURES SHALL BE TAKEN TO INSURE THAT LARGE DELIVERY TRUCKS SERVICING THE SITE DO NOT DAMAGE TO AREAS OF EXISTING VEGETATION OR CAUSE DISTURBANCE TO STABILIZED AREAS.

#### ORDERLY CONSTRUCTION PROCEDURES:

THE CONTRACTOR SHALL PERFORM SITE CONSTRUCTION IN A MANNER WHICH WILL INSURE THE STABILIZATION OF AREAS IN PROXIMITY OF OR TRIBUTARY TO WETLAND AREAS AS SOON AS POSSIBLE.

P. EROSION CONTROL DEVICES SUCH AS HAY BALE BARRIERS, SILT FENCES AND MULCH SHALL BE BROUGHT TO THE SITE AND STOCKPILED PRIOR TO INITIATING CONSTRUCTION.

THE CONTRACTOR SHALL PROVIDE AREAS FOR THE TEMPORARY STORAGE OF CONSTRUCTION DEBRIS. CONSTRUCTION DEBRIS SHALL NOT BE ALLOWED TO ACCUMULATE FOR AN EXTENDED PERIOD OF TIME.

LAND CLEARING SHALL BE PERFORMED IN PHASES CONSISTENT WITH ACTUAL CONSTRUCTION REQUIREMENTS. FINAL LAND CLEARING SHALL BE LIMITED TO RETURN TO GRADE SLOPES.

TREES SHALL BE CUT FOR ENTIRE SITE LEAVING SUMPS IN PLACE TO MAINTAIN SOIL STABILIZATION.

3. STUMPS SHALL BE PULLED AND STOCKPILED FOR GRINDING. BRUSH AND BRANCHES SHOULD BE CHIPPED AND UTILIZED FOR WOOD MULCH IF PRACTICAL.

. VEHICLES UTILIZED IN THE CLEARING OPERATION SHOULD NOT TRAVERSE WETLANDS OR FLOWING BROOKS OR STREAMS WITHOUT PRIOR APPROVAL FROM THE LOCAL CONSERVATION COMMISSION OR AGENT.

ROUGH GRADING:

1. THE ROUGH GRADING OF THE SITE SHALL FOLLOW THE FILL AND EXCAVATION SEQUENCES AS DESCRIBED ON THE CONSTRUCTION PHASING PLANS. SLOPES SHALL BE MAINTAINED AWAY FROM WETLANDS AND SENSITIVE AREAS AS MUCH IS PRACTICAL.

2. DURING THIS PROCESS THE EROSION POTENTIAL IS HIGH. SUFFICIENT EROSION CONTROL BARRIERS SHOULD BE KEPT IN PROXIMITY TO THE WORK AREA TO ALLOW QUICK ACTION SHOULD EROSION BECOME AN ISSUE AND TO INSURE THAT NO SEDIMENT REACHES WETLANDS OR OTHER SENSITIVE AREAS.

3. IN AREAS OF CUT AND/OR FILL WHERE SLOPES COULD DIVERT WATER TOWARD WETLAND AREAS, DIVERSION TRENCHES AND/OR SWALES SHOULD BE CONSIDERED AND IMPLEMENTED TO DIVERT WATER AWAY FROM THESE AREAS.

4. STEEP SIDE SLOPES IN EXCAVATION OR FILL SHOULD BE AVOIDED. DISTURRED AREAS SHALL BE STABILIZED BY LOAMING AND SEEDING

OR RIPRAPPED IMMEDIATELY AFTER THE FINISH GRADE HAS BEEN MET. IF FINAL GRADING DOES NOT OCCUR DURING THE GROWING SEASON, THESE AREAS SHALL BE MULCHED WITH HAY WITH A TACKIFIER, IF NECESSARY SLOPED AREAS MAY REQUIRE ADDITIONAL CONTROLS SUCH AS EROSION CONTROL SOCKS OR HAYBALES.

6. A GROUND COVER SUFFICIENT TO RETAIN SOILS IN A STABILIZED CONDITION MUST BE PROVIDED WITHIN 14 WORKING DAYS, SEASON PERMITTING. ON ANY PORTION OF THE TRACT UPON WHICH FURTHER ACTIVE CONSTRUCTION IS NOT BEING UNDERTAKEN.

1. IF DRAINAGE PIPES OR SWALES ARE TO BE INSTALLED, THEY SHALL BE CONSTRUCTED FROM DOWNSTREAM UP AND CONSTRUCTION SHALL INCLUDE THE PLACEMENT OF OUTFALL RIPRAP AND OTHER MITIGATIVE MEASURES SHOWN ON THE PLAN.

2. PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, HAY BALES OR OTHER SUITABLE METHODS TO ENTRAP SEDIMENT SHALL BE PLACED

3. THE TOE OF EMBANKMENTS SHALL BE STABILIZED IMMEDIATELY, MULCHED AND TACKED DOWN BY SUITABLE MEANS.

#### CREATION OF DETENTION BASIN:

THE DETENTION BASIN HAS BEEN PLACED AS A SEPARATE ITEM TO EMPHASIZE THE IMPORTANCE OF EROSION CONTROL DURING ITS 2. THE PRIMARY EROSION CONTROL METHOD FOR BASIN CONSTRUCTION,

AS WELL AS FOR THE SITE IS THE RAPID STABILIZATION OF ALL SURFACES. SECONDARY IN IMPORTANCE IS THE CONCENTRATION OF RUNOFF BE AVOIDED IN ORDER TO PREVENT THE TRANSPORT OF

3. DURING CONSTRUCTION, THE FILL AND EXCAVATION SEQUENCES SHOWN ON THE CONSTRUCTION PHASING PLANS. ALONG WITH THE DETAILS PROVIDED IN THIS PLAN SET SHALL BE UTILIZED. THESE SEQUENCES REQUIRE THAT SLOPED AREAS LEFT FOR ANY PERIOD OF TIME NOT SLOPED TOWARDS THE WETLAND OR SENSITIVE AREA, BUT RATHER BACK INTO THE FILL MATERIAL.

4. THE BASIN BERM IS TO BE CONSTRUCTED BY EQUIPMENT WORKING ON STABLE MATERIAL ONLY. HAY BALES SHALL BE PLACED AT THE TOE OF SLOPE UNTIL SURFACES ARE STABILIZED.

5. NO EXCAVATION WITHIN THE BASIN SHALL COMMENCE UNTIL THE BERM IS IN PLACE.

6. CARE SHOULD BE TAKEN TO INSURE THAT ORGANIC MATERIAL REMOVED FROM THE BASIN AREA IS RESERVED FOR FINISH GRADING AND THE STABILIZATION OF DISTURBED AREAS.

7. IF DEWATERING IS NECESSARY, PUMPING TO A SETTLING BASIN SHALL BE PERMITTED IF SETTLING BASIN IS CONSTRUCTED, MAINTAINED AND

8. AT NO TIME SHALL RUNOFF CARRYING SEDIMENT BE ALLOWED TO FLOW TO THE WETLANDS OR SENSITIVE AREAS.

9. THE WORK AREA SHALL REMAIN FREE OF LITTER AND DEBRIS AT ALL TIMES AND MONITORED ON A DAILY BASIS TO ENSURE COMPLIANCE. 10. ALL MATERIALS STOCKPILED SHALL BE LOCATED, MULCHED OR OTHERWISE TREATED TO INSURE THAT MATERIALS CONTAINED, THEREIN, AREA NOT CARRIED INTO THE WETLANDS.

11. ANY MATERIALS BLOWN OR CARRIED BY WATER AWAY FROM THE CONSTRUCTION SITE OR INTO THE WETLAND AREAS SHALL BE PROMPTLY REMOVED AS REQUIRED BY THE LOCAL CONSERVATION COMMISSION. 12. A GEOTECHNICAL FILTER FABRIC SHALL BE PLACED OVER THE BASIN SUBDRAIN DURING CONSTRUCTION TO PREVENT SEDIMENT FROM ENTERING AND CLOGGING THE DRAIN. THE FABRIC SHALL BE REMOVED FOR BASIN

#### PREPARATION FOR FINAL STABILIZATION. GRUBBING AND STRIPPING:

PROTECTED AND SUPPLEMENTED.

1. TOP SOIL SHALL BE RETAINED AND STOCKPILED FOR LANDSCAPING


2. GRUBBING AND STRIPPING OF SLOPES LEADING TO WETLAND AREAS SHOULD NOT BE UNDERTAKEN DURING PERIODS OF INTENSE RAINFALL. 3. TOP SOIL STOCKPILE LOCATIONS ARE DEPICTED ON THE SITE DEVELOPMENT PLAN. THE EROSION CONTROL PLAN. AND/OR THE CONSTRUCTION PHASING PLAN AND SHALL BE ADHERED TO.


4. WHEN WORKING IN THE VICINITY OF WETLANDS, TOP SOIL SATURATED WITH WATER SHALL BE REMOVED, AND CONTAINED PRIOR TO BEING USED.

5. AREAS LEADING TO WETLANDS SHALL HAVE HAY BALE BARRIERS INSTALLED ACROSS THEM IN ARCS POINTING DOWN THE HILL AT INTERVALS SUFFICIENT TO MITIGATE RUNOFF CARRYING SEDIMENT. DURING PERIODS OF INTENSE RAINFALL, OR IF THE PROJECT IS TO BE LEFT FOR A PERIOD OF TIME, CONSIDERATION SHOULD BE GIVEN TO SUPPLEMENT HAY BALE BARRIERS WITH EITHER CRUSHED STONE OR

ARMORED BARRIERS. CONSIDERATION MAY ALSO BE GIVEN TO DIVERTING


RUNOFF INTO TEMPORARY SEDIMENTATION CONTROL AREAS. 7. WHENEVER PRACTICAL, NATURAL VEGETATION SHALL BE RETAINED,





12" COMPACTED GRANULAR BASE M1.03.0- TYPE A SUB-BASE MATERIAL, CLEAN FILL COMPACTED TO 95% DRY DENSITY ∼UNDISTURBED EARTH OR SUITABLE MATERIAL ∕ COMPACTED TO 95% DRY DENSITY GRAVEL ACCESS LANE SECTION (FOR ACCESS TO PANELS AND DETENTION BASIN)

NO SCALE - 10FT WIDE




28FT WIDE - NO SCALE

NOTES:

1. ALL CONDUITS TO BE CONSTRUCTED PER THE SPECIFICATIONS OF THE 2. PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, THE CONTRACTOR IS TO NOTIFY EACH UTILITY COMPANY AND OR AGENCY TO DETERMINE THE REQUIREMENTS AND SPECIFICATIONS OF SAID COMPANY OR AGENCY. 3. TRACER TAPE TO BE PROVIDED FOR ALL NONMETALLIC UTILITIES FROM

MAIN LINE TO POINT OF CONNECTION.

EXCAVATION SEQUENCE NO SCALE PHASE PHASE II -EXISTING GRADE WORKING FACE - SHALL ALWAYS LOAM AND SEED EXCAVATED AREAS **EXCAVATION** AS SOON AS POSSIBLE SLOPE AWAY FROM SENSITIVE AREA Water Barrel FINISH GRADE -**EXCAVATED AREA** SENSITIVE AREA WITH FACE AS TO INSURE ENTRAPMENT OF WATER FROM DISTURBED FROM DISTURBED SHOWN IN PHASE 1 WITH FINISH BASE GRADES PHASE III PHASE IV - EXISTING GRADE \*\*\*\* \*\*\* FINISH GRADE-FINISH GRADE -EXCAVATE AS SHOWN IN PHASE 2 LEAVE 2 FOOT HIGH BERM UNTIL GRASS IS ESTABLISHED AT TOE OF BERM LOAM AND SEED & MULCH BERM AREA FILL SEQUENCE NO SCALE PHASE PHASE II—A PLACE MATERIAL WITH SLOPE AWAY FROM SENSITIVE AREAS ONLY AS REQUIRED PRIOR TO PLACEMEN TO PLACEMENT OF MATERIALS SITE LEAVING DIKES UNDISTURBED MATERIAL OR GRADE TO ENTRAP INSTALL SEDIMENT \_\_\_\_\_ ENTRAPMENT DEVICES IN RUNOFF ON A LOCALIZED PROXIMITY OF DISTURBANCE IF MATERIAL CANNOT BE PLACED AS IN PHASE 2-A PHASE II-B PHASE III PLACE MATERIAL WITH SLOPE TO SENSITIVE AREA. BUT, F EROSION POTENTIAL IS FROM EROSION PRESENT. FORM DIKES DIVERT DEVICE TO LIMIT SLOPES AND MULCH INDISTURBED AREA CAPABLE IF REQUIRED OF ALLOWING SEDIMENTATION DEVICE TO RETAIN



**POLYPROPYLENE** 

JIJIIIIIIII XI

TEMPORARY INLET

SEDIMENT FILTER

TEMPORARY INLET SEDIMENT FILTER TO

INSTALLED ON ALL PAVED CATCH BASINS

(800-448-3636) OR ENGINEER APPROVED

OR STORM INLETS. INLET FILTER TO BE SIMILAR TO "SILTSACK" AS

MANUFACTURED BY ATLANTIC

EQUAL CLEAN FILTER AS NEEDED.

CONSTRUCTION FABRICS, INC

-OVERFLOW

INSTALLATION

DUMP STRAP

SILT SACK DETAIL

SILT SACK

BOOT

BITUMINOUS CONCRETE CURB \* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \* SECURE THE STRAW WATTLE WITH WOOD STAKES EVERY 3-4 FEET AND WITH A STAKE AT EACH END. STAKES SHOULD BE DRIVEN THROUGH THE MIDDLE OF THE WATTLE LEAVING 2-3" OF THE STAKE EXPOSED. STAKES SHOULD BE DRIVEN PERPENDICULAR TO THE SLOPE FACE. (SEE STRAW WATTLE DETAIL)

DUMP STRAPS

**EXPANSION** 

(1/4" NYLON

ROPE 2" FLAT

RESTRAINT

WASHERS)

BAG DETAIL

**SPACING** STRAW \*WATTLE 30 FEET 20 FEET SPACING IS - BASED ON SLOPE GRADIENT (SEE TABLE)


. . . . . . . . . \* \* \* \* \* **APPLICANT:** . . . ZPT ENERGY SOLUTIONS II, LLC BRENDON GOVE, MANAGER EROSION CONTROL SLOPE DETAIL

6 PARK AVENUE WORCESTER, MASSACHUSETTS 01605 OWNER: NICHOLAS A. CASELLO & JACQUELINE MATTHEWS 500 BOUTILIER ROAD LEICESTER, MASSACHUSETTS 01524

ADJACENT STRAW

WATTLE SHALL TIGHTLY OVERLAP

**DEFINITIVE PLAN** 



**HANNIGAN** ENGINEERING, INC. CIVIL ENGINEERS & LAND SURVEYORS

8 MONUMENT SQUARE (978) 534-1234 (T LEOMINSTER, MASSACHUSETTS 01453 (978) 534-6060 (F)

CONSTRUCTION DETAILS LEICESTER, MASSACHUSETTS


WWW HANNIGANENGINEERING COM

PREPARED FOR: ZPT ENERGY SOLUTIONS II, LLC BRENDON GOVE 6 PARK AVENUE WORCESTER, MASSACHUSETTS, 01605

TEL: (774) 314-2549

SCALE: NA DRWN: CMA/WDH


CALC: CMA/WDH CHKD: WDH DATE: MAR 20, 201 FB: E2719.070618 JOB NO: 2719 SRV: JEF/IEH **SHEET** 10 **OF** 11 PLAN NO:C-14-2 **TAB:** (10) DET




CONSTRUCTION VEHICLES. CONTRACTOR TO REPLENISH STONE AS NEEDED TO

CONSTRUCTION ENTRANCE

NO SCALE





#### STORMWATER OPERATION AND MAINTENANCE PLAN

THE FOLLOWING SHALL BE CONSIDERED THE OPERATION & MAINTENANCE PLAN (OMP) FOR THE STORMWATER COLLECTION FACILITY FOR THIS DEVELOPMENT. THIS OMP HAS BEEN PREPARED IN ACCORDANCE WITH THE STORMWATER MANAGEMENT POLICY AS ISSUED BY THE DEPARTMENT OF ENVIRONMENTAL PROTECTION.

SYSTEM OWNERSHIP THE SYSTEM SHALL INCLUDE THE DRAINAGE INFRASTRUCTURE AND ALL OF ITS COMPONENTS AS SHOWN ON THE SITE DEVELOPMENT PLANS, INCLUDING THE DETENTION FACILITIES AND OUTFALL AREAS OF THE DRAINAGE SYSTEM. THE STRUCTURES OF THE SYSTEM SHALL INCLUDE THE DRAINAGE SWALES AND THE OUTFALL & CONTROL STRUCTURES. THE SYSTEM SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE CONSTRUCTION DETAILS AND THE APPROVED PLANS.

UPON THE COMPLETION OF CONSTRUCTION THE DRAINAGE SYSTEM DESCRIBED ABOVE AND AS DEPICTED ON THE SITE PLANS SHALL BECOME PROPERTY OF THE LAND OWNER, WITH SPECIFIC EASEMENT RIGHTS TO THE OPERATOR OF THE SOLAR SYSTEM TO MAINTAIN THE DRAINAGE SYSTEM AS DEPICTED ON THE APPROVED PLANS. SAID EASEMENT RIGHTS SHALL BE SPECIFICALLY DESCRIBED IN LEASE DOCUMENTS FOR THE PROJECT.

#### RESPONSIBLE PARTIES

SPILLWAYS

DRAINAGE SWALE

CATCH BASINS

**HYDROWORKS** 

-HYDROGUARD

THE OPERATOR OF THE SOLAR SYSTEM SHALL BE CONSIDERED THE RESPONSIBLE PARTY FOR THE OPERATION AND MAINTENANCE OF THE STORMWATER MANAGEMENT SYSTEM. THE SYSTEM SHALL INCLUDE THE DRAINAGE INFRASTRUCTURE AND ALL OF ITS COMPONENTS AS SHOWN ON THE APPROVED PLANS. THE SYSTEM SHALL ALSO INCLUDE THE DETENTION FACILITIES AND THE OUTFALL AREAS OF THE DRAINAGE SYSTEM.

#### III. INSPECTION & MAINTENANCE SCHEDULE

THE FOLLOWING MAINTENANCE SCHEDULE SHALL BE FOLLOWED IN ORDER TO MAINTAIN THE EFFECTIVENESS OF THE STORMWATER MANAGEMENT SYSTEM.

QUARTERLY AND AT THE QUARTERLY, OR WHENEVER

STRUCTURE TYPE RIP/RAP APRONS TWICE A YEAR SUBDRAINS TWICE A YEAR DETENTION BASINS MONTHLY (MAY-OCT) **OUTFALL STRUCTURES:** TWICE A YEAR

TWICE A YEAR

END OF END OF THE

FOLIAGE AND SNOW

ANNUALLY IN THE

EVERY 4 YEARS MONTHLY (MAY-OCT) EVERY 10 YEARS MONTHLY (MAY-OCT)

THE DEPTH OF DEPOSITS IS


EVERY 10 YEARS

REMOVE DEBRIS & ADD STONE REPLACE PEASTONE MOW GRASS AREAS & REMOVE DEBRIS REMOVE SEDIMENT IF PRESENT REMOVE DEBRIS & ADD STONE REMOVE DEBRIS AND VEGETATION MOW GRASS AS NECESSRY REPLACE STONE AS NECESSARY REMOVE SEDIMENT FROM SUMPS

GREATER THAN OR EQUAL TO \*\*\*GRATES TO BE KEPT CLEAR ONE HALF THE DEPTH FROM THROUGHOUT THE YEAR\*\*\* THE BOTTOM OF THE INVERT OF THE LOWEST PIPE

REMOVE SEDIMENT FROM ANNUALLY IN THE

NOTE: THE DETENTION BASINS ON THIS PROJECT MAY GROW VEGETATION IN THE BOTTOM WHICH MAY INCLUDE SPECIES PART OF THE WETLAND PROTECTION ACT. THESE PLANTS SHALL NOT BE CONSTRUED AS HAVING PROTECTION UNDER THE ACT AND SHALL BE CONSIDERED OPPORTUNISTIC GROWTH PLANTS. ADDITIONALLY, THIS AREA SHALL NOT BE CONSIDERED A CONSTRUCTED WETLAND.




SIGN POST DETAIL (NO SCALE)

S-330" x 30"

**APPLICANT:** ZPT ENERGY SOLUTIONS II, LLC BRENDON GOVE, MANAGER 6 PARK AVENUE WORCESTER, MASSACHUSETTS 01605 OWNER:

NICHOLAS A. CASELLO & JACQUELINE MATTHEWS 500 BOUTILIER ROAD LEICESTER, MASSACHUSETTS 01524

# **DEFINITIVE PLAN**



## HANNIGAN ENGINEERING, INC.

CIVIL ENGINEERS & LAND SURVEYORS

8 MONUMENT SQUARE (978) 534-1234 (T LEOMINSTER. MASSACHUSETTS 01453 (978) 534-6060 (F

# CONSTRUCTION DETAILS LEICESTER, MASSACHUSETTS

PREPARED FOR: ZPT ENERGY SOLUTIONS II, LLC BRENDON GOVE 6 PARK AVENUE WORCESTER, MASSACHUSETTS, 01605 TEL: (774) 314-2549

DRWN: CMA/WDH | SCALE: NA CALC: CMA/WDH APPD: WDH CHKD: WDH DATE: MAR 20, 201 FB: E2719.070618 JOB NO: 2719 SRV: JEF/IEH SHEET 11 OF 11 | PLAN NO:C-14-29 **TAB:** (10) det