
DEFINITIVE SUBDIVISION PLAN

"ROBERT'S WAY"
1355 MAIN STREET
IN
LEICESTER, MASSACHUSETTS
NOVEMBER 30, 2022
REVISIONS THROUGH JANUARY 23, 2023



APPLICANT:

ZP BATTERY DEVCO, LLC BRENDON GOVE 10 E. WORCESTER STREET, SUITE 3A WORCESTER, MASSACHUSETTS 01604

OWNER:

WR ENTERPRISES, LLC 1323 MAIN STREET LEICESTER, MASSACHUSETTS 01420


CIVIL ENGINEER & LAND SURVEYOR:


HANNIGAN ENGINEERING, INC. 8 MONUMENT SQUARE LEOMINSTER, MASSACHUSETTS 01453 TEL: (978) 534-1234


PLAN INDEX

SHEET	1	PLAN OF LAND
SHEET	2	EXISTING CONDITION PLAN
SHEET	3	DEFINITIVE SUBDIVISION PLAN
SHEET	4	ROADWAY PROFILE PLAN
SHFFTS	5-6	CONSTRUCTION DETAILS

PERMITTING SET - NOT FOR CONSTRUCTION







DATE:

APPLICANT:

BRENDON GOVE

OWNER:

ZP BATTERY DEVCO, LLC

WR ENTERPRISES, LLC

1323 MAIN STREET

10 E. WORCESTER STREET, SUIT 3A

WORCESTER, MASSACHUSETTS 01604

LEICESTER, MASSACHUSETTS 01524

LOCUS PLAN

SCALE: 1"=40'

JOB NO: 3010

PLAN NO:C-17-38

DATE: NOV 30,202

CALC: CMA

CHKD: WDH

TAB: (3) SDP

SRV: JEF


SCALE: 1":1000"

DRWN: CMA


APPD: WDH

FB: 71-22

SHEET 3 OF 6




LEICESTER PLANNING BOARD



ROADWAY PROFILE -ROBERT'S WAY

> HORIZONTAL SCALE: 1": 40" VERTICAL SCALE: 1":4"

> > ZP BATTERY DEVCO, LLC BRENDON GOVE 10 E. WORCESTER STREET, SUIT 3A OWNER: WR ENTERPRISES, LLC 1323 MAIN STREET



PROJECT INFORMATION

LAND INFORMATION MAP /PARCEL:

DEED BOOK-PAGE: 65218/149 EXISTING FRONTAGE: 5.44 ACRES EXISTING AREA:

ZONING INFORMATION ZONING DISTRICT:

HIGHWAY BUSINESS-INDUSTRIAL 1 (HB-1) DIMENSIONAL REQUIREMENTS: 60,000 S.F.

MINIMUM AREA: MINIMUM FRONTAGE: MAXIMUM HEIGHT: MINIMUM SETBACKS: FRONT YARD: SIDE YARD:

GENERAL NOTES:

REAR YARD:

PROPERTY LINE INFORMATION BASED DEEDS AND PLANS OF RECORD. NO CERTIFICATION OF PROPERTY LINES SHOWN ON THIS PLAN IS INTENDED OR IMPLIED BY HANNIGAN ENGINEERING, INC. TOPOGRAPHIC INFORMATION IS THE RESULT OF AN ON-THE-GROUND TOPOGRAPHIC SURVEY BY HANNIGAN ENGINEERING, INC. IN JULY OF 2021.

2. AREAS SUBJECT TO PROTECTION UNDER THE WETLANDS PROTECTION ACT HAVE BEEN DELINEATED BY CARON ENVIRONMENTAL CONSULTING ON MARCH 26, 2021. THESE AREAS ARE DEPICTED ON THE PLANS BASED ON FIELD SURVEY LOCATION DURING THE TOPOGRAPHIC SURVEY.

UPON VISIBLE STRUCTURES AT THE TIME OF THE FIELD SURVEY. LOCATION OF EXISTING UTILITIES AND SUBSURFACE STRUCTURES, WHETHER OR NOT SHOWN ON THESE PLANS, SHALL BE DETERMINED BY THE CONTRACTOR, MARKED IN THE FIELD, AND REVIEWED BY THE ENGINEER PRIOR TO THE COMMENCEMENT OF CONSTRUCTION. THE CONTRACTOR SHALL BE AWARE OF THE OBLIGATION TO ALL UTILITY COMPANIES AND AGENCY AS WELL AS DIG-SAFE PRIOR TO EXCAVATION. (SEE NOTE)

3. LOCATION OF ALL UTILITIES ARE APPROXIMATE AS SHOWN AND BASED

4. NOTIFICATION REQUIREMENTS SHOWN ON THIS PLAN SHALL NOT RELIEVE THE CONTRACTOR OF ANY OTHER REQUIREMENTS WHICH MAY EXIST UNDER LOCAL, STATE, OR FEDERAL JURISDICTION TO WHICH THE CONTRACTOR IS

5. RELOCATION OF AND/OR CONNECTION TO EXISTING UTILITIES SHALL BE PERFORMED IN ACCORDANCE WITH PROVISIONS OF THE APPROPRIATE UTILITY COMPANY AND/OR REGULATORY AGENCY. 6. UNLESS OTHERWISE SPECIFIED, ALL MATERIALS AND WORKMANSHIP SHALL

CONFORM WITH THE REQUIREMENTS OF THE TOWN OF LEICESTER AND THE MASS DOT SPECIFICATIONS OF HIGHWAYS AND BRIDGES.

7. ALL SLOPES UNLESS OTHERWISE SPECIFIED, SHALL BE LOAMED AND SEEDED FOR STABILIZATION.

8. ANY DEVIATIONS IN DESIGN AS SHOWN SHALL REQUIRE A REVIEW AND APPROVAL OF THE DESIGN ENGINEER OR FIRM. CHANGES MADE IN THE FIELD MADE WITHOUT AUTHORIZATION SHALL BE SUBJECT TO REVIEW BY ENGINEER AND APPROPRIATE APPROVING AUTHORITY. EXPENSES INCURRED TO BRING THE UNAUTHORIZED CHANGES TO ACCEPTABLE CONFORMANCE SHALL BE BORNE BY THE COMPANY OR CONTRACTOR MAKING THE UNAUTHORIZED CHANGE.

9. ANY MATERIALS DISCOVERED ON-SITE WHICH ARE NOT SUITABLE FOR USE IN THE PROJECT AS SHOWN ON THIS PLAN SHALL BE REMOVED AND HAULED OFF-SITE TO AN APPROPRIATELY LICENSED FACILITY. 10. PLANS TO BE REVIEWED BY APPLICABLE UTILITY AGENCIES FOR

COMPLIANCE WITH REGULATIONS. FINAL LOCATION IS SUBJECT TO CHANGE. 11. APPLICANT SHOULD BE AWARE OF OBLIGATIONS TO COMPLY WITH CHAPTER 131, SECTION 40 OF THE MASSACHUSETTS GENERAL LAWS, OTHERWISE KNOWN AS THE WETLANDS PROTECTION ACT, AND THE ASSOCIATED REGULATIONS (310 CMR 10.00)


12. STOCKPILING OF MATERIAL SHALL NOT BE PERMITTED WITHIN ANY AREAS SUBJECT TO PROTECTION UNDER THE WETLANDS PROTECTION ACT WITHOUT PRIOR APPROVAL BY THE LOCAL CONSERVATION COMMISSION. STOCKPILES SHALL BE PLACED IN A SUITABLE LOCATION AND SURROUNDED BY A ROW OF STAKED HAY BALES FOR EROSION CONTROL.

13. AREAS OF FILL TO BE COMPACTED TO A MINIMUM 95% DRY DENSITY IN AREAS WITHIN ROADWAYS AND UTILITY EASEMENTS. OTHER AREAS OF FILL TO BE COMPACTED TO A MINIMUM 90% DRY DENSITY. ALL FILL MATERIALS ARE TO BE CLEAN FILL, FREE OF DELETERIOUS MATERIALS AND DEBRIS. 14. ALL SIDEWALKS AND RAMPS TO CONFORM TO REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT (ADA), AS REQUIRED. SEE ARCHITECTURAL PLANS FOR CONFORMANCE REQUIREMENTS FOR PROPOSED BUILDINGS. 15. THE AREA PROPOSED FOR DEVELOPMENT IS NOT WITHIN A 100 YEAR FLOOD PLAIN PER F.E.M.A. FIRM PANEL #250313 0781 E, DATED: JULY 4, 2011. COMPLIANCE WITH APPLICABLE REGULATIONS IS REQUIRED.

16. ALL REINFORCED CONCRETE PIPE TO BE CLASS III UNLESS OTHERWISE 17. PRE-CONSTRUCTION CONFERENCE SHALL BE HELD PRIOR TO THE

COMMENCEMENT OF CONSTRUCTION. 18. ALL UTILITIES ARE TO BE INSTALLED BY A LICENSED UTILITY CONTRACTOR LICENSED BY THE TOWN OF LEICESTER.

DEFI		NITIVE PLA	_AN	
1	1/23/23	PEER REVIEW COMMENT	CMA	
NO	DATE	REVISIONS	RY	



|HANNIGAN ENGINEERING, INC.

CIVIL ENGINEERS & LAND SURVEYORS


8 MONUMENT SQUARE LEOMINSTER, MASSACHUSETTS 01453 (978) 534-1234 (T) (978) 534-6060 (F)

ROADWAY PROFILE LEICESTER, MASSACHUSETTS

PREPARED FOR:

ZP BATTERY DEVCO, LLC BRENDAN GOVE

10 E WORCESTER STREET SUITE 3A WORCESTER, MASSACHUSETTS 01604



APPLICANT: WORCESTER, MASSACHUSETTS 01604 LEICESTER, MASSACHUSETTS 01524

EROSION & SEDIMENTATION CONTROL PLAN

. THE PURPOSE OF THIS PLAN IS TO PRESENT A PREVENTIVE METHOD F CONSTRUCTION TO MINIMIZE THE IMPACT OF THE CONSTRUCTION ACTIVITIES UPON WETLAND AND OTHER SENSITIVE AREAS. THE DATA CONTAINED ON THIS PLAN IS INTENDED TO SUPPLEMENT THE DEVELOPER OR CONTRACTORS' EXPERTISE AND IS NOT MEANT TO CIRCUMVENT LOGICAL DECISIONS REQUIRED BY A VARIETY OF FIELD CONDITIONS NCLUDING WEATHER AND THE TYPE OF EQUIPMENT AVAILABLE TO THE

CONTRACTOR.

THE CONTRACTOR IS TO BE AWARE OF THE REQUIREMENTS AND OBLIGATIONS TO COMPLY WITH CHAPTER 131, SECTION 40 OF THE MASSACHUSETTS GENERAL LAWS, OTHERWISE KNOWN AS THE WETLANDS PROTECTION ACT. AND ITS ASSOCIATED REGULATIONS (310 CMR 10.00). CERTAIN PERMITS IN THE FORM OF AN ORDER OF CONDITIONS, OR OTHER FORMAT, MAY BE REQUIRED FOR THE CONSTRUCTION AS DEPICTED ON THIS PLAN. THESE PERMITS SHALL BE REVIEWED AND ADHERED TO BY HE CONTRACTOR THROUGHOUT THE CONSTRUCTION PROCESS. THE CONTRACTOR SHALL ALSO MAINTAIN COPIES OF ALL PERMITS ON SITE

3. IF CHANGES IN THE PROJECT ARE REQUIRED DUE TO FIELD CONDITIONS THE DEVELOPER/CONTRACTOR SHALL PROMPTLY NOTIFY THE NGINEER FOR REVIEW OF THESE CONDITIONS. UPON REVIEW, AND PRIOR THE IMPLEMENTATION OF ANY CHANGE, THE CONTRACTOR AND THE ENGINEER SHALL MEET WITH THE APPROPRIATE LOCAL AND/OR STATE OFFICIAL, OR ITS AGENT, TO DETERMINE IF THE CHANGE REQUIRES MODIFICATION TO EXISTING APPROVED PERMITS.

. ALTERATION AND/OR DESTRUCTION OF WETLAND AREAS WITHOUT PRIOR CONSENT OF THE CONSERVATION COMMISSION IS PROHIBITED. SILTATION PLUMES, ILLICIT DISCHARGES, OR INADVERTANT ALTERATION SHALL BE CONSIDERED AS ACTIVITIES NOT PERMITTED BY THE ORDER AND SHALL BE REPORTED TO THE CONSERVATION COMMISSION ALONG WITH THE PROPOSED MITIGATIVE MEASURES.

PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, THE EROSION AND SEDIMENT CONTROL BARRIER SHALL BE INSTALLED AS SHOWN ON THE PLANS. THE CONTRACTOR SHALL MAINTAIN THE EROSION CONTROL BARRIER UNTIL ALL WORK IS COMPLETE AND ALL AREAS HAVE BEEN STABILIZED. THE REMOVAL OF SEDIMENT CONTROL DEVICES SHALL BE ONLY UPON THE APPROVAL OF THE CONSERVATION COMMISSION.

E. EROSION AND SEDIMENTATION CONTROL DEVICES, SUCH AS CHECK DAMS, SEDIMENT BASINS, ETC. ARE TO BE INSTALLED AS SHOWN ON THE SITE DEVELOPMENT PLANS WITH ASSOCIATED DETAILS, AS APPROPRIATE.

CONSTRUCTION OPERATIONS SHALL NOT CAUSE NOTICEABLE SEDIMENTATION PLUMES TO OCCUR ON OR SURROUNDING THE PROJECT. SHOULD SEDIMENT EXTEND BEYOND THE EROSION CONTROL BARRIERS, E CONTRACTOR SHALL STOP WORK AND INSTALL ADDITIONAL MITIGATION MEASURES TO PREVENT FURTHER SEDIMENTATION.

3. NO MATERIAL SUBJECT TO EROSION SHALL BE STOCKPILED OVERNIGHT WITHIN 100 FEET OF ANY WETLAND AREAS WITHOUT PROPER EROSION AND SEDIMENTATION DEVICES IN PLACE.

D. EQUIPMENT SHALL NOT BE PARKED WITHIN WETLAND OR BUFFER AREAS EXCEPT DURING ACTUAL OPERATIONS REQUIRING SAID EQUIPMENT. . ACCUMULATED SEDIMENT ALONG EROSION CONTROL BARRIERS SHALL E PERIODICALLY REMOVED AND DISPOSED OF BY THE CONTRACTOR AS REQUIRED BY THE CONSERVATION COMMISSION OR AS DIRECTED BY THE

<u>EROSION CONTROL METHODS:</u>

IT IS OF GREAT IMPORTANCE THAT CONCENTRATION OF RUNOFF BE AVOIDED IN ORDER TO PREVENT THE TRANSPORT OF SEDIMENT. THE PRIMARY EROSION CONTROL METHOD TO BE UTILIZED IS TO LIMIT HE AREA OF DISTURBANCE DURING CONSTRUCTION ACTIVITIES. THIS IS CCOMPLISHED BY PROMPT STABILIZATION OF DISTURBED AREAS UPON COMPLETION OF SEQUENCES OF CONSTRUCTION.

EROSION AND SEDIMENT CONTROL DEVICES SUCH AS HAY BALES, SILT ENCES, DIVERSION BERMS, ETC. SHALL BE UTILIZED FOR THE PROTECTION OF THE AREAS BEYOND THE LIMIT OF CONSTRUCTION.

<u>DEMARCATION OF SENSITIVE AREAS:</u>

IT IS RECOMMEND THAT BARRIERS BE PLACED ON THE SITE TO CONTROL THE LIMITS OF THE DISTURBANCE. AS AN EXAMPLE, HAY BALE BARRIERS PROVIDE SUCH DEMARCATION AND OTHER METHODS SUCH AS LOG BARRIERS. ROPE WITH FLAGGING, ETC. MAY BE UTILIZED CARE SHOULD BE TAKEN IN THE OPERATION OF EQUIPMENT, SUCH

. ACCESS TO THE SITE SHALL BE MADE IN THE AREA OF A PERMANENT DRIVEWAY OR ROADWAY UNLESS DOING SO WOULD RESULT IN A TRAFFIC

HAT ONLY THE MINIMUM AREA NEEDED TO BE ALTERED IS DISTURBED.

. AN AREA OF CRUSHED STONE SHALL BE PLACED AT THE DRIVEWAY ENTRANCE TO INSURE THAT MUD IS NOT TRACKED ONTO THE EXISTING ROAD (SEE CONSTRUCTION ENTRANCE DETAIL). IF MUD IS INADVERTENTLY TRACKÈD ONTO THE ROAD, IT SHOULD BE PROMPTLY REMOVED.

LABORERS VEHICLES SHALL BE PARKED IN A DESIGNATED AREA AS O MINIMIZE DISTURBED SURFACES AND TO INSURE THAT RUTS ARE NOT CREATED AND WHICH COULD CARRY WATER TO A WETLAND OR OTHER

. SUITABLE MEASURES SHALL BE TAKEN TO INSURE THAT LARGE DELIVERY TRUCKS SERVICING THE SITE DO NOT DAMAGE TO AREAS OF EXISTING VEGETATION OR CAUSE DISTURBANCE TO STABILIZED AREAS.

<u>ORDERLY CONSTRUCTION PROCEDURES:</u>

THE CONTRACTOR SHALL PERFORM SITE CONSTRUCTION IN A MANNER WHICH WILL INSURE THE STABILIZATION OF AREAS IN PROXIMITY OF OR TRIBUTARY TO WETLAND AREAS AS SOON AS POSSIBLE.

. EROSION CONTROL DEVICES SUCH AS HAY BALE BARRIERS, SILT FENCES AND MULCH SHALL BE BROUGHT TO THE SITE AND STOCKPILED PRIOR TO INITIATING CONSTRUCTION.

THE CONTRACTOR SHALL PROVIDE AREAS FOR THE TEMPORARY STORAGE OF CONSTRUCTION DEBRIS. CONSTRUCTION DEBRIS SHALL NOT BE ALLOWED TO ACCUMULATE FOR AN EXTENDED PERIOD OF TIME.

LAND CLEARING SHALL BE PERFORMED IN PHASES CONSISTENT WITH ACTUAL CONSTRUCTION REQUIREMENTS. FINAL LAND CLEARING SHALL BE LIMITED TO RETURN TO GRADE SLOPES.

TREES SHALL BE CUT FOR ENTIRE SITE LEAVING SUMPS IN PLACE TO MAINTAIN SOIL STABILIZATION.

3. STUMPS SHALL BE PULLED AND STOCKPILED FOR GRINDING. 4. BRUSH AND BRANCHES SHOULD BE CHIPPED AND UTILIZED FOR WOOD MULCH IF PRACTICAL.

VEHICLES UTILIZED IN THE CLEARING OPERATION SHOULD NOT TRAVERSE WETLANDS OR FLOWING BROOKS OR STREAMS WITHOUT PRIOR APPROVAL FROM THE LOCAL CONSERVATION COMMISSION OR AGENT.

LEICESTER PLANNING BOARD

ROUGH GRADING:

1. THE ROUGH GRADING OF THE SITE SHALL FOLLOW THE FILL AND EXCAVATION SEQUENCES AS DESCRIBED ON THE CONSTRUCTION PHASING PLANS. SLOPES SHALL BE MAINTAINED AWAY FROM WETLANDS AND SENSITIVE AREAS AS MUCH IS PRACTICAL.

2. DURING THIS PROCESS THE EROSION POTENTIAL IS HIGH. SUFFICIENT EROSION CONTROL BARRIERS SHOULD BE KEPT IN PROXIMITY TO THE WORK AREA TO ALLOW QUICK ACTION SHOULD EROSION BECOME AN ISSUE AND TO INSURE THAT NO SEDIMENT REACHES WETLANDS OR OTHER SENSITIVE AREAS.

3. IN AREAS OF CUT AND/OR FILL WHERE SLOPES COULD DIVERT WATER TOWARD WETLAND AREAS, DIVERSION TRENCHES AND/OR SWALES SHOULD BE CONSIDERED AND IMPLEMENTED TO DIVERT WATER AWAY FROM THESE AREAS.

4. STEEP SIDE SLOPES IN EXCAVATION OR FILL SHOULD BE AVOIDED. DISTURBED AREAS SHALL BE STABILIZED BY LOAMING AND SEEDING OR RIPRAPPED IMMEDIATELY AFTER THE FINISH GRADE HAS BEEN MET. IF FINAL GRADING DOES NOT OCCUR DURING THE GROWING SEASON, THESE AREAS SHALL BE MULCHED WITH HAY WITH A TACKIFIER. IF NECESSARY SLOPED AREAS MAY REQUIRE ADDITIONAL CONTROLS SUCH AS EROSION CONTROL SOCKS OR HAYBALES.

6. A GROUND COVER SUFFICIENT TO RETAIN SOILS IN A STABILIZED CONDITION MUST BE PROVIDED WITHIN 14 WORKING DAYS, SEASON PERMITTING, ON ANY PORTION OF THE TRACT UPON WHICH FURTHER ACTIVE CONSTRUCTION IS NOT BEING UNDERTAKEN.

1. IF DRAINAGE PIPES OR SWALES ARE TO BE INSTALLED, THEY SHALL BE CONSTRUCTED FROM DOWNSTREAM UP AND CONSTRUCTION SHALL INCLUDE THE PLACEMENT OF OUTFALL RIPRAP AND OTHER MITIGATIVE MEASURES SHOWN ON THE PLAN.

2. PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, HAY BALES OR OTHER SUITABLE METHODS TO ENTRAP SEDIMENT SHALL BE PLACED DOWNSTREAM.

3. THE TOE OF EMBANKMENTS SHALL BE STABILIZED IMMEDIATELY, MULCHED AND TACKED DOWN BY SUITABLE MEANS.

PROTECTED AND SUPPLEMENTED.


1. TOP SOIL SHALL BE RETAINED AND STOCKPILED FOR LANDSCAPING PURPOSES.

2. GRUBBING AND STRIPPING OF SLOPES LEADING TO WETLAND AREAS SHOULD NOT BE UNDERTAKEN DURING PERIODS OF INTENSE RAINFALL. 3. TOP SOIL STOCKPILE LOCATIONS ARE DEPICTED ON THE SITE DEVELOPMENT PLAN, THE EROSION CONTROL PLAN, AND/OR THE CONSTRUCTION PHASING PLAN AND SHALL BE ADHERED TO.

4. WHEN WORKING IN THE VICINITY OF WETLANDS, TOP SOIL SATURATED WITH WATER SHALL BE REMOVED, AND CONTAINED PRIOR TO BEING USED. 5. AREAS LEADING TO WETLANDS SHALL HAVE HAY BALE BARRIERS INSTALLED ACROSS THEM IN ARCS POINTING DOWN THE HILL AT INTERVALS SUFFICIENT TO MITIGATE RUNOFF CARRYING SEDIMENT.


LEFT FOR A PERIOD OF TIME, CONSIDERATION SHOULD BE GIVEN TO SUPPLEMENT HAY BALE BARRIERS WITH EITHER CRUSHED STONE OR ARMORED BARRIERS. CONSIDERATION MAY ALSO BE GIVEN TO DIVERTING RUNOFF INTO TEMPORARY SEDIMENTATION CONTROL AREAS. '. WHENEVER PRACTICAL, NATURAL VEGETATION SHALL BE RETAINED,

6. DURING PERIODS OF INTENSE RAINFALL, OR IF THE PROJECT IS TO BE





STRAW WATTLE & SILT FENCE DETAIL


NO SCALE





(NO SCALE)















& SEED

1. ALL CONDUITS TO BE CONSTRUCTED PER THE SPECIFICATIONS OF THE APPLICABLE UTILITY COMPANY AND/OR AGENCY.

2. PRIOR TO THE COMMENCEMENT OF CONSTRUCTION, THE CONTRACTOR IS TO NOTIFY EACH UTILITY COMPANY AND/OR AGENCY TO DETERMINE THE REQUIREMENTS AND SPECIFICATIONS OF SAID COMPANY OR AGENCY.


3. TRACER TAPE TO BE PROVIDED FOR ALL NONMETALLIC UTILITIES FROM MAIN LINE TO POINT OF CONNECTION.






CLEAN -

DECIDUOUS TREE PLANTING DETAIL NO SCALE



SILT SACK DETAIL



MAINTAIN EFFECTIVENESS.


CONSTRUCTION ENTRANCE NO SCALE

THE USE OF A TEMPORARY COLD PATCH.

4" BITUMINOUS 12" COMPACTED **GRAVEL** SAWCUT PAVEMENT 12" FROM EDGE OF TRENCH CLEAN GRANULAR BACKFILL COMPACTED IN 6" LIFTS SEE TYPICAL PIPE TRENCH -DETAILS FOR TRENCHING REQUIREMENTS UNDISTURBED MATERIAL

AFTER BACKFILLING HAS BEEN COMPLETED AND SUB GRADE REESTABLISHED, A FOUR (4) INCH BITUMINOUS CONCRETE, TYPE I TEMPORARY PATCH SHALL BE INSTALLED AND MAINTAINED UNTIL A PERMANENT PATCH IS INSTALLED (SEE DETAIL).

TEMPORARY PATCH DETAIL NO SCALE



PERMANENT PATCH DETAIL

TRENCH PATCHING NOTES:

1) UPON COMPLETION OF THE TRENCH/UTILITY INSTALLATION WORK, AND ONLY AFTER REQUIRED BACKFILLING AND COMPACTION HAS BEEN ACHIEVED, SHALL ROAD PATCHING OPERATIONS BEGIN. IN NO EVENT SHALL OPENINGS BE ALLOWED TO BE LEFT UN-PATCHED FOR MORE THAN FORTY-EIGHT (48) HOURS WITHOUT WRITTEN APPROVAL OF THE DEPARTMENT OF PUBLIC WORKS

2) ALL ROAD PATCHES SHALL BE PLACED PERPENDICULAR OR PARALLEL TO TRAFFIC FLOW. ANGULAR PATCHES ACROSS THE ROADWAY SHALL NOT BE PERMITTED WITHOUT DPW APPROVAL. ALL TRENCHES SHALL BE SAW-CUT TO PROVIDE A VERTICAL JOINT FOR PATCHING. i) hot patch shall be used at all times except when seasonal conditions warrant

4) IF A TEMPORARY PATCH IS USED, THE DPW SHALL BE NOTIFIED AS TO WHEN A PERMANENT PATCH IS TO BE PLACED. THE CONTRACTOR IS RESPONSIBLE UNTIL THE PERMANENT PATCH IS IN PLACE.

5) TEMPORARY PATCHES SHALL BE MAINTAINED BY THE CONTRACTOR THROUGH ONE WINTER-SPRING SEASON. PERMANENT PATCH WILL BE REQUIRED ON ALL TRENCHES AND SHALL BE WARRANTEED FOR A PERIOD OF ONE YEAR.

6) PERMANENT PATCHES IN A HEAVILY TRAVELED AREA, AS DETERMINED BY THE DPW, SHALL BE REINFORCED WITH A CONCRETE SLAB NO LESS THAN FIVE (5) INCHES THICK. CONSTRUCTION SHALL COMPLY WITH SECTION 430 OF THE COMMONWEALTH OF MASSACHUSETTS DEPARTMENT OF PUBLIC WORKS STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES.

') TEMPORARY AND PERMANENT PATCHES SHALL BE NO LESS THAN FOUR (4) INCHES THICK OR THE THICKNESS OF THE EXISTING PAVEMENT, WHICHEVER IS GREATER.

3) TEMPORARY AND PERMANENT PATCHES SHALL BE ROLLED AND COMPACTED TO MATCH THE ÉXISTING SURFACE IN A GOOD WORKMANLIKE MANNER AND ALL ABUTTING SURFACES SEALED. 9) PERMANENT PATCHES WILL BE MAINTAINED BY THE CONTRACTOR FOR A PERIOD OF NINETY (90) DAYS AT WHICH TIME THE PATCH WILL BE FINALIZED BY THE INFRARED METHOD OF PATCHING. NO INFRARED PATCHING WILL BE REQUIRED ON ANY PAVEMENT THAT IS FIVE (5)


10) ALL MATERIALS AND CONSTRUCTION METHODS MUST MEET THE COMMONWEALTH OF MÁSSACHUSETTS DEPARTMENT OF PUBLIC WORKS STANDARD SPECIFICATIONS FOR HIGHWAYS AND

11) THE REPAINTING OF TRAFFIC LINES SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. THE TOWN SHALL BE NOTIFIED PRIOR TO THE PAINTING OF ANY NEW TRAFFIC MARKINGS. 12) THE CONTRACTOR SHOULD EXERCISE EXTREME CARE TO PREVENT THE DAMAGE TO MAJOR ROOT SYSTEMS OF TREES.

13) WHERE MANHOLES ARE TO BE PLACED IN THE HARDENED SURFACE, ALL MANHOLE COVERS SHALL BE SET IN CONCRETE COLLARS TO WITHIN FOUR (4) INCHES OF THE FXISTING SURFACE. A PATCH OF CLASS I BITUMINOUS PAVEMENT TYPE I SHALL BE PLACED OVER THE CONCRETE COLLAR TO A LEVEL WITH THE PAVEMENT GRADE WHEN SATISFACTORILY COMPACTED. 14) WITH THE EXCEPTION OF EMERGENCY WORK, NO EXCAVATION SHALL BE PERMITTED FROM DÉCEMBER 1 TO APRIL 1. WORK WITHIN THIS PERIOD MAY BE ALLOWED AT THE DISCRETION OF

DEFINITIVE PLAN

PEER REVIEW COMMENT CMANO. DATE BY REVISIONS



HANNIGAN ENGINEERING, INC.

CIVIL ENGINEERS & LAND SURVEYORS

B MONUMENT SQUARE (978) 534-1234 (T) LEOMINSTER, MASSACHUSETTS 01453 (978) 534-6060 (F WWW.HANNIGANENGINEERING.COM

CONSTRUCTION DETAILS LEICESTER, MASSACHUSETTS

PREPARED FOR: ZP BATTERY DEVCO, LLC

BRENDAN GOVE 10 E WORCESTER STREET SUITE 3A WORCESTER, MASSACHUSETTS 01604 TEL:

SHOWING STREET, SHOWING STREET			
	CALC: CMA	DRWN: CMA	SCALE: NA
	CHKD: WDH	APPD: WDH	DATE: NOV 30,2022
200000000000000000000000000000000000000	SRV: JEF	FB: 71–22	JOB NO: 3010
	TAB: (5-6)DET	SHEET 5 OF 6	PLAN N0:C-17-38

